Spinnaker pole sections

The Seldén dinghy spinnaker pole range includes both tapered and parallel alloy poles and a super-stiff light-weight carbon pole.

Carbon pole

The Seldén dinghy carbon spinnaker pole comprises a 39mm parallel tube manufactured on our state-of-the-art filament winding machine, using a customised adaptor for the standard pole end. Its lightweight, tailor-made laminate makes it a must for any development class.

All our dinghy poles are fitted with the newly designed spinnaker pole end. Moulded from high modulus com-

posite, with a stainless steel plunger, this is undoubtedly one of the best pole ends on the market.

Tapered pole

Tapered aluminium spinnaker poles are offered in both 38 and 42 mm centre diameters, tapering down to 25 mm at each end. This gives maximum stiffness in the area of maximum load, yet keeps the pole down to minimum weight. The poles are available in various taper configurations to offer the most efficient pole for your boat.

Parallel poles

Parallel alloy poles are available in 25 and 32 mm diameter tubes, with an adaptor for the 32 mm pole to receive the standard pole end.





| | Art. No. | Description |
|---|------------|--|
| 1 | 534-830-01 | 25 mm dinghy pole end with stainless steel plunger |
| | 534-837 | 32 mm pole adaptor |
| | 534-834 | 39 mm pole adaptor |
| | 534-525-01 | Stainless steel lift eye |
| | 511-241-01 | Ramp |
| | 511-240 | Pole centre cleat |
| | 534-841-01 | Pole lift eye strop for 39 mm pole with 1 x attachment eye |
| | 534-848-01 | Auto pole launch pole end fitting |

Pole extrusions

| Art. No. | Description | Length max. |
|------------|--------------------------------------|--------------|
| 535-510-01 | 25 mm parallel alloy tube | 5 m |
| 535-511-01 | 32 mm parallel alloy tube | 5 m |
| 535-512-03 | 38 mm tapered alloy pole tube | 1480-1825 mm |
| 535-513-06 | 42 mm tapered alloy pole tube | 1670-2000 mm |
| 535-513-04 | 42 mm tapered alloy pole tube | 1850-2230 mm |
| 535-513-05 | 42 mm tapered alloy pole tube | 2240-2480 mm |
| 535-547-02 | 33 mm carbon pole tube | 2600 mm |
| 535-548-01 | 39 mm carbon pole tube | 1730 mm |
| 535-548-02 | 39 mm carbon pole tube | 2000 mm |
| 535-548-03 | 39 mm carbon pole tube | 2600 mm |
| 535-548-04 | 39 mm carbon pole tube (super-stiff) | 2600 mm |