



Halyard kits

Seldén offers complete halyard kits in various dimensions and lengths. The halyard should be completed by your local rigger.

Remove the old halyard and measure it. If the old halyard is no longer available, measure the length of the mast and multiply by two. Check the wire length (if required) and any extra rope if you are going to operate the halyard from the cockpit.

Genoa halyards, 16/16 plaited polyester rope, 7x19 wire

| Art. No. | Wire dia./length mm | Rope blue dia./length, mm | Snap shackle |
|------------|---------------------|---------------------------|--------------|
| 602-001-06 | 3/10000 | 8/13000 | 307-203 |
| 602-002-14 | 4/13000 | 10/16500 | 307-204 |
| 602-003-14 | 5/15000 | 12/19000 | 307-338 |
| 602-004-10 | 6/17000 | 12/21000 | 307-338 |



Genoa halyard kit.



Main halyard kit.

Main halyards, 16/16 plaited polyester rope, 7x19 wire

| Art. No. | Wire dia./length mm | Rope white dia./length, mm | Shackle |
|------------|------------------------|-------------------------------|---------|
| 602-001-07 | 3/10000 | 8/13000 | 307-003 |
| 602-002-15 | 4/13000 | 10/16500 | 307-005 |
| 602-003-15 | 5/15000 | 12/19000 | 307-021 |
| 602-004-11 | 6/17000 | 12/21000 | 307-024 |